

P32M

32 Channel 1080P HD-TVI DVR



- Full Gui With Alpha Blending
- Individual Setting Of Resolution, Frame Rates And Picture Quality
- Instant Replay
- Digital Zoom (Live & Playback)
- Mouse Control
- Weekly Scheduler With Holiday By 10 Minutes Setting
- Covert, Disable And Private Function Of Cameras
- Motion Detection With 352 Area Settings
- Relay Alarm Output
- PTZ Control By RS-485
- Daylight Saving Time And Network Time Setting
- Multi-User Authority Up To 8 Users
- De-Interlacer Upon Live And Playback
- 22 Languages With Full Graphic
- Individual Network Port Setting
- Auto Deletion
- Import And Export The Configuration
- Mirroring
- POS Interface
- Dual Codec Engine For Independent Video Transmission
- Interactive Setup via Network



Model		P32M	
Video	Camera input	32 BNC	
	Individual HD/Analog selectable	All Hybrid	
	Available source	TVI 720p/25,30/1080p/25,30/Composite/960H/Mixed	
	IP Camera	Spec	ONVIF 2.3, RTSP, H.264, dual stream use gigabit ethernet hub
		Num	4
Restriction		Cannot display HD SPOT, SPOT Cannot setup Private ZONE Cannot attach email image Cannot snapshot live image Cannot support Timestamp	
Output	1 HDMI (Main Display or Programmable HD Spot) 1 VGA (Main Display or Programmable HD Spot) 1 Composite (Programmable SPOT)		
Audio	Audio input	16 RCA	
	Output	1 RCA	
Sensor In		16 (NC, NO selectable)	
Alarm out		2 Relay, 14 TTL	
Operating System		Embedded Linux OS	
Display	Speed	Real Time	
	Resolution (Pixel)	1280X1024, 1280X720, 1920X1080	
	Split screen	1,4,6,8,9,13,16	
Main Recording	Resolution (Pixel)	1080p, 720p, 960x540 (1080p/25,30) 720p, 960x540 (720p/25,30) 960H, D1, 480x240, CIF (Composite, 960H)	
		Picture quality	4 steps (Super, High, Medium, Low)
		Speed	NTSC area PAL area
		480fps@720p/480fps@1080p 400fps@720p/400fps@1080p	
Dual Recording	Condition	Main Recording is 1080p, 720p	
	Resolution (Pixel)	480x256	
Playback	Display	1,4,6,8,9,13,16,25,32	
	Search mode	Calendar, Event, POS, Panorama, Thumbnail	
	Speed	NTSC area PAL area	
		480fps@1080p 400fps@1080p	
	Fast/Slow speed	Normal, REW & FF [recorded speed x2, x4, x8, x16, x32, x64, x1/2, x1/4], Frame to frame, Pause	
Network (Individual setting of resolution, frame rates and picture quality)	Network Interface	Gigabit Ethernet x 2	
	High Resolution (Pixel)	1080p, 720p(1080p/25,30) 720p, 960x540 (720p/25,30) 960H, D1 (Composite, 960H)	
		Low Resolution (Pixel)	480x256 (1080p/25,30) 480x256 (720p/25,30) CIF (Composite, 960H)
	Speed	NTSC area PAL area	
		180fps@1080p 140fps@1080p	
	Protocol	TCP/IP, HTTP, DHCP	
	Application	Windows 7 / 8 (PC Client system& IE)/MAC	
	Web Browser	Internet Explorer, Safari, Chrome, Firefox	
Smart phone App	Android, iPhone for live and search		
Backup	Interface	USB 2.0 X 3	
	Backup device	External HDD, CD&DVD-RW, Network, Thumb Drive	
The number of HDD		4 SATA + 1 eSATA(upto 12 bays, No capacity limit ; 4TB or more)	
Others	Power Consumption	150W	
	Operating Temp.	5 ~40°C(41~104F)	
	Relative Humidity	Maximum 80% non-condensing	
	Dimension	430(W)×420(D)×88(H)mm	